



PRODUCT GUIDE

www.kensaheatpumps.com



Version 3.5

Kensa Shoebox & Shoebox Twin

The world's smallest & quietest ground source heat pump



✓ 3kW - 6kW

✓ Single Phase

✓ Space saving

✓ Silent

✓ RHI eligible

✓ Water to 65°C



- The Kensa Shoebox series features the quietest and smallest ground source heat pump on the market.
- Available in a 3kW single compressor model and 6kW twin compressor model, the award-winning Kensa Shoebox series is an efficient, practical and affordable heating solution engineered to provide both heating and hot water in new build and retrofit multi-dwellings and starter homes.
- Designed to displace gas combination boilers as the default choice for smaller properties, the Shoebox is the first ground source heat pump solution that can be comfortably installed inside any home due to its low sound levels, output and size.

Small in size, big in space, time & cost savings

Install inside the home

The Kensa Shoebox is designed to fit in the under-sink kitchen cupboard in individual flats and apartments, providing a discreet and independent heating solution.

Quick and low cost install

The Kensa Shoebox is easy for any plumber to install, plus when paired with a shared ground loop array approach, permits lower cost and quicker ground works due to a smaller number of shallower boreholes, resulting in more efficient project delivery.

RHI Eligible

When paired with Kensa's shared ground loop array approach, Shoebox installations benefit from the Non-Domestic Renewable Heat Incentive for 20 years. Individual Shoebox installations that are retrofit or self build and do not feature shared ground loops receive the Domestic Renewable Heat Incentive (RHI) for 7 years.

Kensa Evo

An evolutionary new ground source heat pump series



✓ 7kW - 17kW

✓ Water to 60°C

✓ Low noise

✓ RHI eligible

✓ Single phase

✓ Three phase



- The ERP A++ rated Evo series delivers heating and hot water efficiencies of MCS SCOPs of up to 4.7 at 35°C, along with industry leading noise reduction.
- Offering a 15 per cent gain in efficiency in order to minimise running costs and maximise income via the Renewable Heat Incentive.

Featuring Kensa custom-built controls unique to ground source heat pumps.

- In-built sensors and probes enable remote commissioning and live status readings via a unique control board, featuring an intuitive touch screen that facilitates parameter settings and pre-empts system irregularities.
- With cross head screws in its unique bevelled front panel, the Evo's electrical component and wiring terminals are easily accessible.
- The ergonomic steel casing has been designed with a focus on ease of installation, whilst providing stylish protection.
- Curved cut outs, vertical and horizontal pipe exit points and rear connections offer installation flexibility.

Kensa Twin Compact & Hybrid



✓ 12kW - 30kW

✓ Water to 60°C

✓ Single Phase

✓ Three Phase

✓ High Temperature

✓ RHI eligible



→ Fitted with two compressors, Kensa's Twin Compact and Hybrid series provides greater heat output for larger domestic and small to medium sized commercial applications.

→ Uniquely, the Twin Compact series goes up to 30kW, including a 24kW single phase model; the largest single phase ground source heat pump on the market.

→ Twin Compact models are capable of providing heating and hot water or cooling, and are also available in High Temperature models for the benefit of retrofit applications and high heat demands.

→ The Hybrid series blends the efficiency of a standard Twin Compact with a High Temperature Twin Compact. This results in efficient space heating and higher water temperatures, without the need for direct electric hot water top-up.

The largest single phase ground source heat pump

The Twin Compact series includes a 24kW single phase model; the largest available on the market, providing a wider array of applications.

Kensa Commercial Plant Room



✓ 20 kW– 75kW

✓ Modular

✓ Three Phase

✓ High Temperature

✓ RHI eligible

✓ BMS suitable



Heavy weight class

- Modular combinations for greater flexibility to meet your commercial heating needs.
- The Commercial Plant Room heat pump range is comprised of modular three phase Kensa ground source heat pumps, designed to fit together to provide tailored outputs for high heat demand, providing a greater flexibility to match the heat pump output to the load of a commercial building.
- Plant Room models are available in a range of sizes from 20kW – 75kW modules, which can be modified to provide cooling as well as heating; so one single system can satisfy a building's heating and cooling requirements.

Modular adaptability

With multiple units, it is possible to provide heating and cooling to different parts of a building simultaneously via a Building Management System (BMS).

The multiple unit approach also offers a degree of redundancy in the unlikely event of a problem with one of the units.

Easy interface

Kensa Plant Rooms have been specified to allow straightforward interface with a building's heating distribution system, such as fan coils, underfloor, and air handling units.

Refreshing solution

Upon request Kensa Plant Rooms can be designed as reverse cycle modules which can provide heating or cooling.

Technical specifications

	Shoebox	
Phase	Single	
Nominal thermal kW rating	3	6
MCS Approved	✓	✓
SCOP at 35°C*	3.68	3.45
Performance 35°C	A+	A+
Performance 55°C	A+	A+
Max flow temperature °C**	65	
Rated voltage	220 - 240 V / 50 - 60 Hz	
Starting current amps ***	30	34
H x W x D (mm)	530 x 475 x 370	560 x 605 x 565

	Evo				
Phase	Single				Three
Nominal thermal kW rating	7	9	13	17	15
MCS Approved	✓	✓	✓	✓	✓
SCOP at 35°C*	4.72	4.64	4.40	4.06	4.47
ErP rating at 35°C	A++	A++	A++	A++	A++
ErP rating at 55°C	A++	A++	A++	A+	A++
Max flow temperature °C**	62			55	63
Rated voltage	220 - 240 V / 50 - 60 Hz				380 - 420 V*
Starting current amps ***	18.2	28.7	41.3	45	74
H x W x D (mm)	1160 x 555 x 575				

*50-60Hz

	Twin Compact						High Temp	Hybrid		
Phase	Single			Three			Single			
Nominal thermal kW rating	16	20	24	20	24	30	12	17	15	21
MCS Approved	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
SCOP at 35°C*	3.99	3.82	3.87	4.15	3.83	3.69	3.98	4.03	4.14	3.93
ErP rating at 35°C	A++	A+	A+	A++	A+	A+	A++	A++	A++	A+
ErP rating at 55°C	A+	A+	A+	A+	A+	A+	A+	A+	A+	A+
Max flow temperature °C**	55						65			
Rated voltage	240 V / 50 - 60 Hz			400 V / 50 - 60 Hz			220 - 240 V / 50 - 60 Hz			
Starting current amps ***	44	44	48	55	68	79	42	42	52	60
H x W x D (mm)	900 x 900 x 570									

	Plantroom						HT
Phase	Three						
Nominal thermal kW rating	25	30	40	45	60	70	25
MCS Approved	✓	✓	✓	✓	✗	✗	✓
SCOP at 35°C*	3.75	3.85	3.82	3.75	†	†	3.91
ErP rating at 35°C	A+	A+	A+	A+	†	†	A+
ErP rating at 55°C	A+	A+	A+	A+	†	†	A+
Max flow temperature °C**	50						65
Rated voltage	400 V / 50 - 60 Hz						
Starting current amps ***	57	75	89	101	112	140	54
H x W x D (mm)	1750 x 800 x 900						

Note: Design flow rates are for a ground temperature of 0 and -4°C and a load temperature of 30 and 35°C.

* The SCOP figure quoted is calculated as per EN14825. ** By increasing the flow temperature from the heat pump the efficiency of the unit will drop and the COP decreases.

*** Kensa heat pumps incorporate smart starts as standard to limit the starting current of the compressors. † Units are currently being ErP tested and will be available when complete.

For full details on our entire product range visit www.kensaheatpumps.com

Accessories



Antifreeze

Efficient heat transfer

Readily biodegradable, Thermax DTX is an ethylene glycol substance that has been tested and classified as Non Toxic by an EPA certified laboratory.

The Thermax DTX product incorporates synergistic inhibitors and biocides to prevent scale, corrosion and biological growth, and has high heat transfer and low viscosity characteristics. It can also be mixed with standard mono ethylene glycol to top up existing ground arrays.



Buffer tanks & Cylinders

Design flexibility

Buffer vessels are available in a range of sizes to create a store of energy for space heating. Kensa has partnered with a leading Cylinder Manufacturer to design and produce buffer vessels designed for use with heat pumps. Featuring a 100l compact unit for space saving.

Stainless steel mains pressure cylinders featuring enhanced surface area coils designed specifically for heat pumps and 3 bar operation provide a store of mains pressure water on demand to support the heat pump system. Also available in twin coil units.



Manifolds

Above and below ground

Available in a range of sizes, featuring quality water resistant components, Kensa manufacture above ground manifolds to provide ease of installation and adaptability.

Subterranean manifolds are manufactured from tough, water-resistant polyethylene and are available in a range of sizes with differing numbers of inlets and outlets with control valves, flow meters and fill and bleed ports.



Slinkies

Quick and easy installation

Kensa manufacture slinkies in 30m, 40m and 50m lengths. Featuring a unique pre-coiled assembly, Kensa slinkies ensure quick and easy installation.

Manufactured using black High Density Polyethylene pipe, with a pressure rating of PE80, Kensa slinkies are durable and leak tested prior to dispatch.

All slinkies are supplied with 25m of header pipe.

Kensa Heat Pumps have started a heating revolution and we want you to be a part of it.

The Underground Movement aims to inspire the adoption of ground source heat pumps across the UK by educating end users and potential installers about their significant benefits, and encouraging people to dig deeper and know their sources when it comes to heat pump technology.

Kensa Approved Installations



Kensa's Underground Network of approved installers delivers quality and professional installations in accordance with stringent Kensa specifications and MCS standards.

Join the Underground Movement at
www.kensaheatpumps.com/goingunderground

GET IN TOUCH

Kensa Heat Pumps Ltd, Mount Wellington, Chacewater, Truro, Cornwall TR4 8RJ

Call **0345 222 4328** | Email info@kensaheatpumps.com

Visit www.kensaheatpumps.com

facebook.com/KensaHeatPumps | twitter.com/KensaHeatPumps | youtube.com/KensaHeatPumps

